





EasyPrime

Polyurethane-acrylate water-based sealer for hardwood flooring.

Emissions

	Approval number Z-157.10-19	According to DIBt (German institute for building technology)
	Emicode® EC1, very low emission	According to GEV (Community Emission Controlled Flooring Adhesives and Construction Products e.V., Düsseldorf)
	Meets interior emission criteria	According to various US regulations

Technical evaluation

US Regulatory VOC	< 232 g/l
-------------------	-----------

Glossar

DIBt

For reasons of health protection, the German Institute for Building Technology (DIBt) requires a general building supervisory approval for all building products used for the treatment and bonding of parquet on site. Certified building materials are marked with the Ü symbol. This obligation to obtain approval has been in force in Germany since 1 January 2011. In order to obtain approval, compliance with emission limits must be proven and the formulations must be disclosed to the DIBt. www.dibt.de

GEV Emission Code

The EMICODE® symbol identifies building materials and products that emit no or very low fugitive emissions into the indoor air. The award is made by GEV, Gemeinschaft Emissionskontrollierter Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V. The GEV was founded in 1997 by industrial companies to promote products that are harmless to health and the environment. External test institutes certified according to ISO 17025 test the emission behaviour of parquet varnishes. In addition, parquet lacquers with a high solvent content are not approved for testing. This means that the needs of users and residents alike are taken into account. Products marked with EMICODE® are checked regularly. www.emicode.de

AirQuality Seal

Products that meet LOBA's Air Quality Seal meet interior emission criteria

- of the California Section 01350 specification,
- the Collaborative for High Performance Schools (CHPS),
- the Indoor Advantage Gold™ Certification and
- the FloorScore label for low-emission elastic and hard floor coverings

US Regulatory VOC

Article 1113 was adopted in September 1977. The aim of this regulation is to limit the content of volatile organic compounds (VOCs) in architectural paints. Any person who supplies, sells, offers for sale or manufactures architectural coatings for use in SCAQMD must comply with the current VOC standards.



EasyPrime

Notes

Notice

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to special conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.