



TECHNICAL BULLETIN

DURA SEAL® QUICK DRY SEALER

PRODUCT DESCRIPTION: Quickly and conveniently seals wood floors to prepare them for finishing. This product provides a firm bond between the wood floor substrate and succeeding finish coats, and meets the definition for a quick dry sealer by method ASTM D 1640.

RECOMMENDED USE: Wood Floors.

WARNING! Removal of old paint by sanding, scraping, or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

DIRECTIONS:

SURFACE PREPARATION:

1. Sand floors according to NOFMA or NWFA specifications.
2. Vacuum thoroughly and tack the floor. If desired, apply **DURA SEAL® Penetrating Finish** in your choice of color and allow product to dry thoroughly, per label directions.

APPLICATION:

1. Apply **DURA SEAL® Quick Dry Sealer** with a natural China bristle brush or lambswool applicator at a coverage rate of 500 square feet per gallon.
2. Allow surface to dry thoroughly (e.g. 1-1/2 to 2 hours.) Note: Drying time will be increased by high humidity, low temperature, lack of air movement or heavier application.
3. Buff surface with a new 180 grit screen or used 150 grit screen; vacuum thoroughly and tack.
4. Apply the appropriate number of **DURA SEAL® Polyurethane finish** coats to achieve the desired look and durability.

CLEAN-UP: Clean with mineral spirits or paint thinner.

STORAGE: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame.

PHYSICAL PROPERTIES:

SOLVENT: Mineral Spirits

DRY TIME: Dry to the touch within 30 minutes. Ready for re-coating within 2 hours. Meets ASTM D 1640

SHEEN	Gloss
COVERAGE:	Approximately 500 square feet per gallon.
SPECIFIC GRAVITY/DENSITY:	0.85 – 0.87
PRODUCT WEIGHT (LBS/GAL):	7.10 – 41.50
% SOLIDS:	39.50 – 41.50
VOC (g/l):	525 Max.
VISCOSITY	Less than 100 cps.
FLASHPOINT (TTC):	103-F

SAFETY:	- HMIS RATING:	Health	2
		Flammability	2
		Reactivity	0

- **PHYSICAL PRECAUTIONS:** Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.
- **HEALTH:** Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

SIZE	SKU #	CASE/PACK
QUART	86560	6
GALLON	81560	4
5 GALLON	85560	1