

TECHNICAL INFORMATION

EasyFillPro



Fast drying, water-based binder designed to be mixed with your fine wood dust to create a customized wood filler.

- Excellent coverage
- Fast drying
- No offensive odor
- Easy application
- Suitable for all types of wood

Recommended use:


EasyFillPro can be mixed with wood dust from any species and used with engineered, solid, strip, plank or parquet floors. The viscosity can be adjusted from a low viscosity for full troweling to a high viscosity for spot-filling large gaps and spaces. The dried material powders well, sands easily, and won't clog your abrasives. Since the natural material of the floor is being used Easy Fill Pro also stains very consistently without the fear of color loss as seen with many other premixed products.



Technical Data

Art.-no.
11039

Item-#:
LO-FI-261



Solids

30 ±2%

Storage and transportation

Shelf life: 12 months in unopened containers. Store and transport between 40°F to 75°F (5°C to 25°C). KEEP FROM FREEZING.

US Regulatory VOC

< 93 g/l



TECHNICAL INFORMATION

EasyFillPro



Application

- For professional Use only!
- BEFORE USING, READ AND UNDERSTAND ALL LABEL INSTRUCTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our LOBA-WAKOL Technical Service at 1-800.230.6456.
- Sand and prepare floors according to NWFA instructions.
- **WARNING!** If you scrape, sand or remove old paint from wood floors, you may release lead dust. Follow local and/or federal requirements for lead removal. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.
- ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE AND DESIRED RESULTS.
- Shake material well before use.
- Do not thin. Do not add water.
- Do not apply at temperatures below 55°F (12°C). Make sure material is at room temperature. Always maintain adequate ventilation during all phases of the coating and drying process.
- Do not use dust from the belt/drum sander (big machine). Use fine dust from edger or multi-head sander.
- Mix EasyFill Pro with very fine wood dust from sanding into a smooth trowelable consistency. Use the finest dust available. Fine dust will be easier to trowel, fill gaps/voids, and will also provide better adhesion in the joints. Trowel-fill the complete floor before the final sanding. Repeat procedure on larger joints or damaged areas after the first application is fully dry.
- Completely sand all dried material from the surface during your final sanding phase.

Application Tool

LOBATOOL trowel

Coverage

On newly installed hardwood floors with small gaps approx. 500-800 sqft/gal

Screen and Recoat

Do NOT use EasyFill Pro on Factory Finished or Manually Finished Floors. Only for the application directly on raw wood. EasyFill Pro must be overcoated with LOBADUR® waterbased finishes or LOBASOL® oil systems.

Drying time

- On newly installed hardwood floors sandable after 15-30 minutes, at renovations with extremely wide joints let dry over night.
- It is possible to apply Water-based LOBADUR® systems & LOBASOL® oil systems as early as after 1 hour application of Loba EasyFill Pro.

Possible surface treatment with:

Any Water-based LOBADUR® finish system or any LOBASOL® oil system, without limitation.

02/12/2020



TECHNICAL INFORMATION

EasyFillPro



Application

Recommended Procedure for wood floors:

- Sand to your medium grit sanding sequence.
- Trowel-fill with EasyFill Pro
- Allow to dry 20-40 min.
- Final Cut
- Surface treatment according to Technical Information of the product.

Tip: An ideal color result is achieved at a mixing ratio of 1:10 by weight or 2:5 by volume (sanding dust content to binder).

Coloring of dark wood species:

The coloring of dark woods can be improved by adding Mixol universal tinting paint. Pour 1 Gal. of LOBADUR EasyFillPro into a bucket, add 200 ml max. of MIXOL and stir with a paint mixer to a uniform consistency. In order to avoid colour deviations, always mix sufficient mass for a continuous surface.

- **Mixol 23 - Dark Brown** For dark wood types like: smoked oak, wenge, pangapanga
- **Mixol 20 - Chestnut** For reddish wood species such as: jatoba, merbau, mahogany

Compatibility

When this product is used in combination with other LOBA products the Technical Information of these products have to be followed. Always prepare test areas to determine suitability of other products than LOBA.

02/12/2020



TECHNICAL INFORMATION

EasyFillPro



General guidelines

Cleaning of tools: Clean tools and equipment with water.

Cure Time: The stated drying and cure times are based on ideal conditions 68°F (20°C), 65% rH at the recommended application rates. Recommended conditions are 50°F-80°F (10°C to 27°C) /40%-75%rH. Insufficient ventilation, high humidity, lower temperatures, increased coat thickness can prolong the curing process considerably. Do not cover floors, replace carpets or rugs, or clean floors with a damp mop/cloth before the final curing has been reached.

Use with or without a primer: Some finishes can be used without a primer. The use of a primer increases application reliability and decreases risk of application marks on most wood types. Further details can be found in the LOBA wood type list in the current product catalog.

Side bonding: Water-based coating systems usually show a tendency for side bonding. Several measures can be taken to minimize the formation of irregular joints and the associated locking effect. The use of shear-resistant or permanently elastic adhesive to glue the hardwood flooring, careful filling of the joints, use of suitable primers, such as LOBADUR WS EasyPrime. Taking steps to ensure that the room climate, in particular the relative humidity, remains constant. (Education of the customer is recommended). The risk of side bonding is greater with old floors with damaged, weak, or very flexible adhesives and wood flooring installed over underfloor heating, and woods which change their moisture content quickly, such as beech and maple.

Safety Precautions: Even when working with low or zero-emission products the usual safety measures must be taken. Keep away from children. Do not eat, drink or smoke in working areas. Wear suitable safety gloves. Clean left-overs off of hands. Change soiled clothes.

First Aid: If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If breathing is difficult or other respiratory complaints, remove to fresh air and get medical attention. In case of eye contact, immediately flush eyes for several minutes under running water. Generally this product does not cause skin irritation. Call a physician if irritation occurs.

Special Information The information in this document and any other information or advice we provide is intended for our customers only, and all information and advice is subject to the terms and limitations in Loba-Wakol's General Terms and Conditions, including without limit its limited warranty ("Terms"). The Terms are not expanded, changed or waived by the information in this document or by any information or advice given by Loba-Wakol. Loba-Wakol has no relationship or obligation to anyone other than the customer that originally purchases the product from Loba-Wakol. The information in this document and any other information or advice we provide is the result of our prior experience and our knowledge of our products. Due to the wide variety of application possibilities and processing conditions, it is the customer's responsibility to test our product for suitability for its intended purpose. When in doubt, call our Technical Service for support. Technical Information is also available by visiting our website www.loba-wakol.com. You must read and understand, and have your professional installer read and understand, all information contained in our Terms and in our published specifications, technical data sheets, written directions for installation, use and maintenance, and labels on the product. If you have any questions during application or use, immediately stop the application and use and contact our Technical Service. For information about other products offered by Loba-Wakol, please check the technical information concerning those products.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.

02/12/2020

