

Product Datasheet

ADHESIVE

PALLMANN P13

Tongue & Groove Adhesive

PRODUCT DESCRIPTION:

Quick-drying dispersion wood adhesive for gluing the tongue and groove on prefinished wood and laminate flooring. Also suitable for use as a universal wood adhesive on many wood species and wood-based materials.



FEATURES - BENEFITS:

- ▶ Excellent for gluing wood plugs and dowels
- ▶ For indoor use only
- ▶ Solvent-free

TECHNICAL DATA:

| | |
|------------------|--|
| Packaging: | 28.5 oz plastic bottle |
| Shelf life: | 12 months |
| Color: | White |
| Coverage: | 80 – 500 lineal feet per bottle depending on joint size |
| Working climate: | Above 60 °F (surface temp.) |
| Drying time: | 5 – 10 minutes |
| Final strength: | After 1 – 2 days |
| VOC | < 40 g/L |

At 68°F and 65% relative humidity

APPLICATION:

Cut off nozzle tip to fit desired joint size. Apply P13 to the surface of the tongue or into the groove. Join wood parts together during dry time, applying force if necessary with a wooden tapping block and/or straps. Remove all traces of extruded glue immediately with a damp cloth or PALLMANN® Clean Box.

PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

Read and follow all safety and environmental precautions and instructions on the packaging label and the Safety Data Sheet (SDS). The SDS is available at www.pallmann.us.

DISPOSAL:

For disposal and recycling, follow the applicable laws and regulations. Do not allow the material to get into sewers, waterways or unlined ground surfaces. Empty packaging may be recyclable.

INDOOR AIR QUALITY INFORMATION

VOC content: < 40 g/L, compliant with SCAQMD Rule 1168